


Rubber coated systems

NdFeB magnetic system, black rubber sheath, as a complete system with hook or eyelet



Article number	D mm	H mm	HGes mm	Thread M	Adhesive force* N	Shear force* N	Weight g	Temperature °C	Description
A22A-KsHM4 neu	22	6	30	M4	58	18	16	60	Hook
AS022NDOE04S-01 neu	22	6	30	M4	58	18	15	60	Eyelet
A31A-KsHM4 neu	31	6	30	M4	89	25	28	60	Hook
AS031NDOE04S-01 neu	31	6	30	M4	89	25	27	60	Eyelet
A43A-KsHM4 neu	43	6	29	M4	100	38	35	60	Hook
AS043NdOe04s-00 neu	43	6	28	M4	100	38	34	60	Eyelet
A66A-KsHM5 neu	66	8,5	40	M5	250	85	112	80	Hook
A66A-KsÖM5 neu	66	8,5	38	M5	250	85	110	80	Eyelet

PRODUCT NOTE:

These systems are particularly suitable for use on sensitive surfaces. The special rubber coating prevents scratches or discolouration on the surface. The displacement forces are also higher due to the rubber coating.

As an alternative to the standard system, we also offer customised solutions:

- " Other colours for the rubber coating
- " Harder or softer rubber coating

¹ There is a cylinder bore on the adhesive surface due to the manufacturing process.

* The forces have been determined at room temperature on a polished plate made of steel (S235JR according to DIN 10 025) with a thickness of 10 mm (1kg~10N). A deviation of up to -10% from the specified value is possible in exceptional cases. In general, the value is exceeded. The type of application (installation situation, temperatures, counter anchors, etc.) sometimes influence the forces enormously. The values given are for orientation purposes. Let our experts advise you.