


Rubber coated systems

NdFeB magnetic system, black rubber sheath, as complete system with hook or eyelet, rectangular



Article number	L mm	B mm	H mm	HGes mm	Thread M	Adhesive force* N	Shear force* N	Weight g	Temp. °C	Description
AS035NDHK04S-01 neu	35	22,5	6	30	M4	93	36	26	80	Hook
AS035NDOE04S-01 neu	35	22,5	6	30	M4	93	36	25	80	Eyelet
AS055NDHK04S-01 neu	55	22,5	6	30	M4	140	50	36	80	Hook
AS055NDOE04S-01 neu	55	22,5	6	30	M4	140	50	36	80	Eyelet
AS059NDHK05S-01 neu	59	45	8,5	40	M5	240	90	94	80	Hook
AS059NDOE05S-01 neu	59	45	8,5	37	M5	240	90	92	80	Eyelet

PRODUCT NOTE:

These systems are particularly suitable for use on sensitive surfaces. The special rubber coating prevents scratches or discolouration on the surface. The displacement forces are also higher due to the rubber coating.

As an alternative to the standard system, we also offer customised solutions:

- " Other colours for the rubber coating
- " Harder or softer rubber coating

¹ There is a cylinder bore on the adhesive surface due to the manufacturing process.

* The forces have been determined at room temperature on a polished plate made of steel (S235JR according to DIN 10 025) with a thickness of 10 mm (1kg~10N). A deviation of up to -10% from the specified value is possible in exceptional cases. In general, the value is exceeded. The type of application (installation situation, temperatures, counter anchors, etc.) sometimes influence the forces enormously. The values given are for orientation purposes. Let our experts advise you.